

# Fabric specification

# Bison

Fabric type	<b>Artificial leather</b>
Composition	<b>100% polyester</b>
Weight (g/m <sup>2</sup> )	<b>380 ± 5% g/m<sup>2</sup></b>
Width (cm)	<b>142 ± 1cm</b>

TEST TYPES	TEST METHOD	RESULT
Martindale abrasion	ISO 12947-2	<b>&gt; 100.000</b>
Seam slippage	ISO 13936-2	<b>warp - 3.3mm / weft - 4.6mm</b>
Colour fastness dry/wet	ISO 105-X12	<b>dry - 4/5 / wet - 4</b>
Colour fastness to light	ISO 105-B02	<b>5</b>
Tear strength	ISO 13937-3	<b>warp &gt; 35N / weft &gt; 35N</b>
Tensile strength	ISO 13934-1	<b>warp &gt; 720N / weft &gt; 250N</b>
Pilling	ISO 12945-2	<b>5</b>

OEKO-TEX® environmental standard	<b>OEKO-TEX® STANDARD 100</b>
FR standards	<b>BS5852 Source 0; EN1021-1</b>

CARE INSTRUCTIONS	
Wash	<b>30 degrees, gentle cycle</b>
Iron	<b>No</b>
Tumble dry	<b>No</b>
Bleach	<b>No</b>
Dry clean	<b>Yes</b>
Squeeze	<b>No</b>
Keep away from direct sun	<b>If possible</b>

Comments	<b>Color shades may slightly vary from dye-lot to dye-lot</b>
----------	---